

## \* NOTICES \*

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1.This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

---

## DESCRIPTION OF DRAWINGS

---

[Brief Description of the Drawings]

[Drawing 1]It is structural drawing of a surface acoustic wave resonator showing the 1st example of this invention.

[Drawing 2]It is structural drawing showing the conventional surface acoustic wave resonator.

[Drawing 3]It is a sectional view showing the manufacturing process of drawing 1.

[Drawing 4]It is a schematic illustration showing the magnetization work of drawing 1.

[Drawing 5]It is a figure showing the surface acoustic wave resonator of drawing 1 carried in the stem.

[Drawing 6]It is a figure showing the frequency characteristic of the surface acoustic wave resonator of drawing 1.

[Drawing 7]It is a figure showing the frequency characteristic of the surface acoustic wave resonator of the 2nd example of this invention.

[Description of Notations]

11 Piezoelectric board

12 Underlay

13 Input terminal

14 Output terminal

15 IDT

20 Insulator layer

21 The thin film of a ferromagnetic

30 Electromagnet

40 Stem

B Ferromagnetic material layers

---

[Translation done.]